



Warm climate and Medium temperature

Model(s):	CTC GSi 608		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VI -
Brine-to-water heat pump:	Yes	Controller contribution:	4 %
Low-temperature heat pump:	No	Package efficiency:	150 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	7	kW	Seasonal space heating energy efficiency	η_s	146	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	na	kW	T _j = -7 °C	<i>COP_d</i>	na	-
T _j = +2 °C	<i>P_{dh}</i>	6,9	kW	T _j = +2 °C	<i>COP_d</i>	2,84	-
T _j = +7 °C	<i>P_{dh}</i>	4,7	kW	T _j = +7 °C	<i>COP_d</i>	3,68	-
T _j = +12 °C	<i>P_{dh}</i>	2,3	kW	T _j = +12 °C	<i>COP_d</i>	4,64	-
T _j = bivalent temperature	<i>P_{dh}</i>	6,9	kW	T _j = bivalent temperature	<i>COP_d</i>	2,84	-
T _j = operation limit temperature	<i>P_{dh}</i>	6,87	kW	T _j = operation limit temperature	<i>COP_d</i>	2,84	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	2	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,98	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,023	kW	Rated heat output	<i>P_{sup}</i>	0,0	kW
Thermostat-off mode	<i>P_{TO}</i>	0,023	kW	Type of energy input: Electric			
Standby mode	<i>P_{SB}</i>	0,000	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	Variable			-	na	<i>m³/h</i>	
Sound power level, indoors/outdoors	<i>L_{WA}</i>	34/na	<i>dB</i>	-	0,9	<i>m³/h</i>	
Annual energy consumption	<i>Q_{HE}</i>	2443	<i>kWh</i>				

For heat pump combination heater:

Declared load profile	XL			Water heating energy efficiency/Energy class	$\eta_{wh/-}$	98/A	%
Daily electricity consumption	<i>Q_{elec}</i>	8,255	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	1716	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted. Specific precautions/manuals can be found at <http://www.ctc.se/nedladdningar>



Warm climate and Low temperature

Model(s):	CTC GSi 608		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VI -
Brine-to-water heat pump:	Yes	Controller contribution:	4 %
Low-temperature heat pump:	No	Package efficiency:	210 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	7	kW	Seasonal space heating energy efficiency	η_s	206	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	na	kW	T _j = -7 °C	<i>COP_d</i>	na	-
T _j = +2 °C	<i>P_{dh}</i>	7,4	kW	T _j = +2 °C	<i>COP_d</i>	4,56	-
T _j = +7 °C	<i>P_{dh}</i>	4,6	kW	T _j = +7 °C	<i>COP_d</i>	5,40	-
T _j = +12 °C	<i>P_{dh}</i>	2,7	kW	T _j = +12 °C	<i>COP_d</i>	6,39	-
T _j = bivalent temperature	<i>P_{dh}</i>	7,3	kW	T _j = bivalent temperature	<i>COP_d</i>	4,56	-
T _j = operation limit temperature	<i>P_{dh}</i>	7,3	kW	T _j = operation limit temperature	<i>COP_d</i>	4,56	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	2	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,98	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,023	kW	Rated heat output	<i>P_{sup}</i>	0,0	kW
Thermostat-off mode	<i>P_{TO}</i>	0,023	kW	Type of energy input: Electric			
Standby mode	<i>P_{SB}</i>	0,000	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	Variable			-	na	na	m ³ /h
Sound power level, indoors/outdoors	<i>L_{WA}</i>	34/na	dB	-	1,2	1,2	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	1745	kWh				

For heat pump combination heater:

Declared load profile	XL			Water heating energy efficiency/Energy class	$\eta_{wh/-}$	98/A	%
Daily electricity consumption	<i>Q_{elec}</i>	8,255	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	1716	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ

Specific precautions and end of life information: The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted. Specific precautions/manuals can be found at <http://www.ctc.se/nedladdningar>

Average climate and Medium temperature

Model(s):	CTC GSi 608		
Air-to-water heat pump:	No	Energy efficiency class:	A+++ -
Water-to-water heat pump:	No	Controller class:	VI -
Brine-to-water heat pump:	Yes	Controller contribution:	4 %
Low-temperature heat pump:	No	Package efficiency:	163 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	A+++ -
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	7	kW	Seasonal space heating energy efficiency	η_s	159	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	5,6	kW	T _j = -7 °C	<i>COP_d</i>	3,02	-
T _j = +2 °C	<i>P_{dh}</i>	4,3	kW	T _j = +2 °C	<i>COP_d</i>	4,71	-
T _j = +7 °C	<i>P_{dh}</i>	2,3	kW	T _j = +7 °C	<i>COP_d</i>	4,46	-
T _j = +12 °C	<i>P_{dh}</i>	2,3	kW	T _j = +12 °C	<i>COP_d</i>	4,86	-
T _j = bivalent temperature	<i>P_{dh}</i>	6,9	kW	T _j = bivalent temperature	<i>COP_d</i>	2,66	-
T _j = operation limit temperature	<i>P_{dh}</i>	6,87	kW	T _j = operation limit temperature	<i>COP_d</i>	2,84	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-10	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,97	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,023	kW	Rated heat output	<i>P_{sup}</i>	0,0	kW
Thermostat-off mode	<i>P_{TO}</i>	0,023	kW	Type of energy input Electric			
Standby mode	<i>P_{SB}</i>	0,000	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	Variable			-	na	0,9	m ³ /h
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	34/na	dB	-	0,9		m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	3467	kWh				

For heat pump combination heater:

Declared load profile	XL			Water heating energy efficiency/Energy class	$\eta_{wh/-}$	98/A	%
Daily electricity consumption	<i>Q_{elec}</i>	8,255	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	1716	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted. Specific precautions/manuals can be found at <http://www.ctc.se/nedladdningar>

Average climate and Low temperature

Model(s):	CTC GSi 608		
Air-to-water heat pump:	No	Energy efficiency class:	A+++ -
Water-to-water heat pump:	No	Controller class:	VI -
Brine-to-water heat pump:	Yes	Controller contribution:	4 %
Low-temperature heat pump:	No	Package efficiency:	212 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	A+++ -
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	7	kW	Seasonal space heating energy efficiency	η_s	208	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	6,0	kW	T _j = -7 °C	<i>COP_d</i>	4,75	-
T _j = +2 °C	<i>P_{dh}</i>	3,6	kW	T _j = +2 °C	<i>COP_d</i>	5,68	-
T _j = +7 °C	<i>P_{dh}</i>	2,5	kW	T _j = +7 °C	<i>COP_d</i>	5,97	-
T _j = +12 °C	<i>P_{dh}</i>	2,6	kW	T _j = +12 °C	<i>COP_d</i>	6,05	-
T _j = bivalent temperature	<i>P_{dh}</i>	7,3	kW	T _j = bivalent temperature	<i>COP_d</i>	4,56	-
T _j = operation limit temperature	<i>P_{dh}</i>	7,3	kW	T _j = operation limit temperature	<i>COP_d</i>	4,56	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-10	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,97	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,023	kW	Rated heat output	<i>P_{sup}</i>	0,0	kW
Thermostat-off mode	<i>P_{TO}</i>	0,023	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,000	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	Variable			-	na	<i>m³/h</i>	
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	34/na	<i>dB</i>	-	1,2	<i>m³/h</i>	
Annual energy consumption	<i>Q_{HE}</i>	2683	<i>kWh</i>				

For heat pump combination heater:

Declared load profile	XL			Water heating energy efficiency/Energy class	$\eta_{wh/-}$	98/A	%
Daily electricity consumption	<i>Q_{elec}</i>	8,255	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	1716	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted. Specific precautions/manuals can be found at <http://www.ctc.se/nedladdningar>

Contact details

EnerTech AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000

www.ctc.se

200331

Cold climate and Medium temperature

Model(s):	CTC GSi 608		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VI -
Brine-to-water heat pump:	Yes	Controller contribution:	4 %
Low-temperature heat pump:	No	Package efficiency:	166 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	7	kW	Seasonal space heating energy efficiency	η_s	162	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	4,42	kW	T _j = -7 °C	<i>COP_d</i>	4,01	-
T _j = +2 °C	<i>P_{dh}</i>	2,3	kW	T _j = +2 °C	<i>COP_d</i>	4,59	-
T _j = +7 °C	<i>P_{dh}</i>	2,4	kW	T _j = +7 °C	<i>COP_d</i>	5,15	-
T _j = +12 °C	<i>P_{dh}</i>	2,7	kW	T _j = +12 °C	<i>COP_d</i>	5,92	-
T _j = bivalent temperature	<i>P_{dh}</i>	6,9	kW	T _j = bivalent temperature	<i>COP_d</i>	2,88	-
T _j = operation limit temperature	<i>P_{dh}</i>	6,87	kW	T _j = operation limit temperature	<i>COP_d</i>	2,84	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-22	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,97	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,023	kW	Rated heat output	<i>P_{sup}</i>	0,0	kW
Thermostat-off mode	<i>P_{TO}</i>	0,023	kW	Type of energy input Electric			
Standby mode	<i>P_{SB}</i>	0,000	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	Variable			-	na	<i>m³/h</i>	
Sound power level, indoors/ outdoors	<i>L_{WA}</i>	34/na	<i>dB</i>	-	0,9	<i>m³/h</i>	
Annual energy consumption	<i>Q_{HE}</i>	4065	<i>kWh</i>				

For heat pump combination heater:

Declared load profile	XL			Water heating energy efficiency/Energy class	$\eta_{wh/-}$	98/A	%
Daily electricity consumption	<i>Q_{elec}</i>	8,255	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	1716	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted. Specific precautions/manuals can be found at <http://www.ctc.se/nedladdningar>

**Cold climate and Low temperature**

Model(s):	CTC GSi 608		
Air-to-water heat pump:	No	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VI -
Brine-to-water heat pump:	Yes	Controller contribution:	4 %
Low-temperature heat pump:	No	Package efficiency:	221 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
Rated heat output (*)	<i>P_{rated}</i>	7	kW	Seasonal space heating energy efficiency	η_s	217	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T _j				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T _j			
T _j = -7 °C	<i>P_{dh}</i>	4,2	kW	T _j = -7 °C	<i>COP_d</i>	5,52	-
T _j = +2 °C	<i>P_{dh}</i>	2,7	kW	T _j = +2 °C	<i>COP_d</i>	6,11	-
T _j = +7 °C	<i>P_{dh}</i>	2,6	kW	T _j = +7 °C	<i>COP_d</i>	6,14	-
T _j = +12 °C	<i>P_{dh}</i>	2,6	kW	T _j = +12 °C	<i>COP_d</i>	6,14	-
T _j = bivalent temperature	<i>P_{dh}</i>	7,3	kW	T _j = bivalent temperature	<i>COP_d</i>	4,56	-
T _j = operation limit temperature	<i>P_{dh}</i>	7,32	kW	T _j = operation limit temperature	<i>COP_d</i>	4,56	-
For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>P_{dh}</i>	na	kW	For air-to-water heat pumps: T _j = -15 °C (if TOL < -20 °C)	<i>COP_d</i>	na	-
Bivalent temperature	<i>T_{biv}</i>	-22	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	na	°C
Cycling interval capacity for heating	<i>P_{cych}</i>	na	kW	Cycling interval efficiency	<i>COP_{cyc}</i>	na	-
Degradation co-efficient	<i>C_{dh}</i>	0,97	-	Heating water operating limit temperature	<i>WTOL</i>	65	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P_{OFF}</i>	0,023	kW	Rated heat output	<i>P_{sup}</i>	0,0	kW
Thermostat-off mode	<i>P_{TO}</i>	0,023	kW	Type of energy input	Electric		
Standby mode	<i>P_{SB}</i>	0,000	kW				
Crankcase heater mode	<i>P_{CK}</i>	0,000	kW				
Other items							
Capacity control	Variable			For air-to-water heat pumps: Rated air flow rate, outdoors	-	na	m ³ /h
Sound power level, indoors/outdoors	<i>L_{WA}</i>	34/na	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	1,2	m ³ /h
Annual energy consumption	<i>Q_{HE}</i>	3063	kWh				

For heat pump combination heater:

Declared load profile	XL			Water heating energy efficiency/Energy class	$\eta_{wh/-}$	98/A	%
Daily electricity consumption	<i>Q_{elec}</i>	8,255	kWh	Daily fuel consumption	<i>Q_{fuel}</i>	na	kWh
Annual electricity consumption	<i>AEC</i>	1716	kWh	Annual fuel consumption	<i>AFC</i>	na	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted. Specific precautions/manuals can be found at <http://www.ctc.se/nedladdningar>